

Xiaodu (Hangzhou) Trading Co.Ltd

Add: No.909 Huachuang Building, Binjiang District, Hangzhou, Zhejiang, China

CATALOGUE



SURED^o

Tel: +86-571-87920026

Fax: +86-571-85785363

Mob: +86-15988922962

Email: usuredo@usuredo.com

Web: www.usuredo.com

COMPANY

PROFILE

Xiaodu (Hangzhou) Trading Co., Ltd. was founded in 2019, in the near of world famous company Alibaba. We are dedicated to the sales of sprayers, generators high pressure washers and the products in the field of agricultural and garden.

We are a new export trading company with backup of our factory in Taizhou, which has 20 years experience in producing and exporting the sprayers. We are supported by a group of big factories, which are professional in developing and producing generators and high pressure, etc.

We are able to offer the high quality products with competitive prices.

All of our factories are ISO9001 registered and most of our products are CCC, CE and GS approved.

They could also reach the special standards required by different countries and regions.

So we are able to meet the requirements of all kinds of customers.

Good service is our key point, our sales team are well-trained and have good command of English and some other languages. Proficiency in Products knowledge and foreign trade skills.

We can give our customer best support and service.



Pressure Washer

- **Household Series** 01-08
 - OL Series 01-02
 - LT Series 03-07
- **Accessories** 08-08
- **Industrial Series** 09-10

CONTENTS



Generator

- **Inverter Series** 11-14
 - SBI Series 11-14
- **Gasoline Series** 11-18
 - LT Series 15-18
- **Diesel Series** 19-21
 - LT Series 19-21

OL SERIES



601 SERIES

Features:


- Tri-axial plunger pump
- Tempered stainless steel plungers
- Total stop system
- Built-in thermal protector
- Light weight and handle for easy movement
- Rotary ON/OFF switch for convenient use

Standard accessories:



Optional accessories:

- Turbo nozzle
- Fixed brush
- Rotary brush
- Patio cleaner
- Water inlet hose
- Water inlet hose connector
- Soap bottle




602 SERIES

Features:

- Tri-axial plunger pump
- Tempered stainless steel plungers
- Total stop system
- Built-in thermal protector
- Light weight and handle for easy movement
- Rotary ON/OFF switch for convenient use

Standard accessories:



Optional accessories:

- Turbo nozzle
- Fixed brush
- Rotary brush
- Patio cleaner
- Water inlet hose
- Water inlet hose connector
- Soap bottle

Model	OL 601A	OL 601B
Rated Pressure	90bar/100bar/110bar	
Max.Pressure	145bar	
Rated Flow	5.5L/min	
Max.Flow	6.5L/min	
Motor Power	1500W/1700W/1800W	
Volt/Freq.	AC 220-240V~50/60Hz AC120-127V~50/60Hz	
Motor Type	Carbon Brush Motor	
Product Size	298*288*756mm	358*288*500mm
Carton Size	310*300*780mm	370*300*525mm
N.W./G.W.	8.7/10.4kgs	8.5/9.7kgs
Load Quantity(20'/40'/40'HQ)	856/1744/1962	

Model	OL 602A	OL 602B
Rated Pressure	90bar/100bar/110bar	
Max.Pressure	145bar	
Rated Flow	5.5L/min	
Max.Flow	6.5L/min	
Motor Power	1500W/1700W/1800W	
Volt/Freq.	AC 220-240V~50/60Hz AC120-127V~50/60Hz	
Motor Type	Carbon Brush Motor	
Product Size	298*288*756mm	358*288*500mm
Carton Size	310*300*780mm	370*300*525mm
N.W./G.W.	8.7/10.4kgs	8.5/9.7kgs
Load Quantity(20'/40'/40'HQ)	856/1744/1962	

LT SERIES

201

202

203



201/202/203 SERIES

Features:

- 3 Axial-piston wobble-plate pump
- Tempered stainless steel plungers
- Total stop system
- Self-resetting thermal cut-out
- All accessories with quick-connect design
- Portable design with handle for easy movement

Standard accessories:



Optional accessories:

- Turbo nozzle
- Fixed brush
- Rotary brush
- Patio cleaner
- Water inlet hose
- Water inlet hose connector
- Soap bottle

A

B



3 SERIES

Features:

- 3 Axial-piston wobble-plate pump
- Tempered stainless steel plungers
- Total stop system
- Self-resetting thermal cut-out
- All accessories with quick-connect design
- Portable design with handle for easy movement

Standard accessories:



Optional accessories:

- Turbo nozzle
- Fixed brush
- Rotary brush
- Patio cleaner
- Water inlet hose
- Water inlet hose connector
- Soap bottle

Model	LT201/202/203-1200	LT201/202/203-1200
Rated Pressure	70bar	80bar
Max.Pressure	100bar	110bar
Rated Flow	5.5L/min	5.5L/min
Max.Flow	6.5L/min	6.5L/min
Motor Power	1200W	1400W
Volt/Freq.	AC220-240V~50/60Hz ,AC120-127V~50/60Hz	AC220-240V~50/60Hz ,AC120-127V~50/60Hz
Motor Type	Carbon brush motor	Carbon brush motor
Product Size	266*231*391mm(201);265*235*394mm(202);266*231*391mm(203)	264*231*391mm(201);265*235*394mm(202);266*231*391mm(203)
Carton Size	245*230*413mm(201/202);250*240*360mm(203)	245*230*413mm(201/202);250*240*360mm(203)
N.W./G.W.	4.7/5.3kgs	4.9/5.5kgs
Load Quantity(20'/40'/40"HQ)	1249/2500/2700(201/202);1242/2592/3024(203)	

Model	LT3-1200	LT3-1400
Rated Pressure	70bar	80bar
Max.Pressure	100bar	110bar
Rated Flow	5.5L/min	5.5L/min
Max.Flow	6.5L/min	6.5L/min
Motor Power	1200W	1400W
Volt/Freq.	AC220-240V~50/60Hz ,AC120-127V~50/60Hz	AC220-240V~50/60Hz ,AC120-127V~50/60Hz
Motor Type	Carbon brush motor	Carbon brush motor
Product Size	407*222*244mm	407*222*244mm
Carton Size	425*280*275mm	425*280*275mm
N.W./G.W.	4.7/5.3kgs	4.9/5.5kgs
Load Quantity(20'/40'/40"HQ)	856/1744/1962	

LT SERIES

A



B



501 SERIES

Features:

- 3 Axial-piston wobble-plate pump
- Tempered stainless steel plungers
- Total stop system
- Self-resetting thermal cut-out
- All accessories with quick-connect design
- With wheel and handle for easy movement

Standard accessories:



Optional accessories:

- Turbo nozzle
- Fixed brush
- Rotary brush
- Patio cleaner
- Water inlet hose
- Water inlet hose connector
- Soap bottle

A



B



C



503 SERIES

Features:

- 3 Axial-piston wobble-plate pump
- Tempered stainless steel plungers
- Total stop system
- Self-resetting thermal cut-out
- All accessories with quick-connect design
- With wheel and handle for easy movement

Standard accessories:



Optional accessories:

- Turbo nozzle
- Fixed brush
- Rotary brush
- Patio cleaner
- Water inlet hose
- Water inlet hose connector
- Soap bottle

Model	LT501-1600	LT501-1800
Rated Pressure	90bar	100bar
Max.Pressure	130bar	140bar
Rated Flow	6.0L/min	6.0L/min
Max.Flow	7.0L/min	7.0L/min
Motor Power	1600W	1800W
Volt/Freq.	AC220-240V~50/60Hz ,AC120-127V~50/60Hz	
Motor Type	Carbon brush motor	
Product Size	353*282*781mm (A); 353*282*781mm (B)	
Carton Size	340*315*505mm (A); 340*315*630mm (B)	
N.W./G.W.	7.3/8.4kgs(A);7.6/9.2kgs(B)	7.4/8.6kgs(A);7.7/9.3kgs(B)
Load Quantity(20'/40'/40'HQ)	550/1100/1210(A);426/852/968(B)	

Model	LT503-1600	LT503-1800
Rated Pressure	90bar	100bar
Max.Pressure	130bar	140bar
Rated Flow	6.0L/min	6.0L/min
Max.Flow	7.0L/min	7.0L/min
Motor Power	1600W	1800W
Volt/Freq.	AC220-240V~50/60Hz ,AC120-127V~50/60Hz	
Motor Type	Carbon brush motor	
Product Size	353*282*781mm (A); 353*282*781mm (B)	
Carton Size	340*315*505mm (A); 340*315*630mm (B)	
N.W./G.W.	7.3/8.4kgs(A);7.6/9.2kgs(B)	7.4/8.6kgs(A);7.7/9.3kgs(B)
Load Quantity(20'/40'/40'HQ)	550/1100/1210(A);426/852/968(B)	

LT SERIES

ACCESSORIES

701



LT701-2000

701G



LT701G-2100

701 SERIES

Features:

- 3 Axial-piston wobble-plate pump
- Tempered stainless steel plungers
- Total stop system
- Self-resetting thermal cut-out
- All accessories with quick-connect design
- Portable design with handle for easy movement

Standard accessories:



Optional accessories:

- Turbo nozzle
- Fixed brush
- Rotary brush
- Patio cleaner
- Water inlet hose
- Water inlet hose connector
- Soap bottle

LT701G-2100

LT701G-2500

	LT701-2000	LT701-2200	LT701G-2100	LT701G-2500
Rated Pressure	110bar	120bar	110bar	130bar
Max.Pressure	160bar	170bar	160bar	195bar
Rated Flow	6.5L/min	6.5L/min	7.0L/min	7.0L/min
Max.Flow	7.5L/min	7.5L/min	7.8L/min	7.8L/min
Motor Power	2000W	2200W	2100W	2500W
Volt/Freq.	AC220-240V~50/60Hz ,AC120-127V~50/60Hz		AC220-240V~50/60Hz ,AC120-127V~50/60Hz	AC220-240V~50Hz,AC220V~60Hz
Motor Type	Carbon brush motor		Induction motor	
Product Size	394*355*881mm (A);407*355*881mm (B)		394*355*881mm (A);407*355*881mm (B)	
Carton Size	410*370*585mm (A); 390*370*905mm (B)		410*370*585mm (A); 390*370*905mm (B)	
N.W./G.W.	10.5/12.3kgs(A);11.2/14.7kgs(B)	10.7/12.6kgs(A);11.4/15.0kgs(B)	18.6/20.4kgs(A);19.3/23.1kgs(B)	20.3/21.9kgs(A);21/24.5kgs(B)
Load Quantity(20'/40'/40'HQ)	309/627/684(A);208/430/504(B)			



G25



G30



G50



G70



G30/G50 Turbo Nozzle



N02 45° Angle Nozzle



N10 Angle Nozzle



N05 45° Angle Spray Nozzle



C01 PVC high pressure hose



C02 PU high pressure hose



C03 Steel armed high pressure hose



QC02 Water Inlet Connector



F01 Water Inlet Filter



F02 Water Inlet Filter



F03 Water Inlet Filter



QC03 3/4 Water Inlet Connector(brass)



QC01 Quick connector



B05 Rotary brush kit



B06 Fix brush kit



B01 Patio Brush Kit



B02 Patio Brush Kit



S01 Soap Bottle



S02 Soap Bottle



G80
G70

LT SERIES

LT-16MA/MB/MB3



3WZ-18060B

Features:

- Four poles electric motor fits overload protection
- Motor with aluminum casing
- Commercial grade direct drive brass cylinder ceramic plungers radial direction pump
- 8m high-pressure hose
- Quick connect nozzles 0°,15°,40° and chemical nozzle
- Pressure adjustable
- Professional trigger gun with safety lock
- 7-inch Semi-filled wheel
- In-line water filter
- Convenient hose and gun hook
- Water inlet hose connector
- Plastic cover
- Protection box
- 5m cable

Standard accessories :



Optional accessories :

- Custom-made motor Voltage and Frequency

LT-19M



3WZ-1507C/3WZ-1508C



3WZ-18127B

Features:

- Four poles electric motor fits overload protection
- Motor with aluminum casing
- Commercial grade direct drive brass cylinder ceramic plungers radial direction pump
- 8m high-pressure hose
- Quick connect nozzles 0°,15°,40° and chemical nozzle
- Pressure adjustable
- Professional trigger gun with safety lock
- 7-inch Semi-filled wheel
- In-line water filter
- Convenient hose and gun hook
- Water inlet hose connector
- Plastic cover
- Protection box
- 5m cable

Standard accessories :



Optional accessories :

- Custom-made motor Voltage and Frequency

Model	LT-16MA	LT-16MB	LT-16MB3
Max. Pressure	80bar	90bar	80bar
Max. Pressure	1160PSI	1300PSI	1160PSI
Rated Flow	12.8L/min	12.8L/min	15.4L/min
Rated Flow	3.38GPM	3.38GPM	4.06GPM
Motor Power	1800W	2200W	2200W
Voltage	AC~220V	AC~220V	AC~380V
Revolution	2900rpm	2900rpm	2900rpm
Pump Model	3WZ-18060B	3WZ-18060B	3WZ-18060B
Carton Size	580*420*395mm	580*420*395mm	580*420*395mm
N.W./G.W.	31kgs/33.6kgs	32kgs/34.2kgs	32kgs/34.2kgs

Model	LT-19MA	LT-19MB	LT-19MC	LT-19ME	LT-19MF
Max. Pressure	120bar	120bar	170bar	180bar	206bar
Max. Pressure	1750PSI	1750PSI	2470PSI	2600PSI	3000PSI
Rated Flow	14.0L/min	14.0L/min	14.0L/min	10.7L/min	12.3L/min
Rated Flow	3.71GPM	3.71GPM	3.71GPM	2.84GPM	3.25GPM
Motor Power	3000W	3000W	4000W	3700W	4000W
Voltage	AC~380V	AC~220V	AC~380V	AC~220V	AC~380V
Revolution	1450rpm	1450rpm	1450rpm	2900rpm	2900rpm
Pump Model	3WZ-18127B	3WZ-18127B	3WZ-18127B	3WZ-1507C	3WZ-1508C
Carton Size	660*510*450mm	660*510*450mm	660*510*450mm	660*510*450mm	660*510*450mm
N.W./G.W.	52kgs/54kgs	54kgs/56kgs	57.5kgs/59.5kgs	55kgs/57kgs	55kgs/57kgs

SBI1000i /1200i



FEATURES:

- 4stroke, 50cc, OHV Engine;
- Powerful and Portable;
- Advanced Inverter Technology;
- Pulse Width Modulation provides Super Clean Power;
- Smart Throttle automatically adjusts engine speed to match the load;
- Fuel efficient up to 8+hours on 0.8gal of gasoline;
- AC/DC Output and Cables for 12V marine batteries charging;
- Non-fuse type circuit breaker(NFB)prevents internal circuit ove-load damage.
- Indicator Light for Output Operation.Low Oil Alarm,Over Load Protection;
- 57db at 7m, ultra-quiet performance due to Noise Block body design.

Model	1000i	1200i
Engine	Single-Cylinder,OHV,4-Stroke,Air-Cooled	
Displacement	50cc	50cc
Ignition system	C.D.I	C.D.I
Starting system	Recoil	Recoil
Frequency(Hz)	50/60	50/60
Voltage(V)	110/120/230/240	110/120/230/240
D.C. Output	12V 5A	12V 5A
A.C. Output	110/120VRated8A 230/240VRated4A	110/120VRated8A 230/240VRated4A
Rated Power Output(W)	900	900
Max. Power Output(W)	1000	1000
Starting Power(W)	1100	1100
Fuel Tank Capacity	3L 0.8GAL	6L 1.6GAL
Continuous Operating Hours	4+hours@rated load/8+hours@1/4 load	4+hours@rated load/8+hours@1/4 load
Noise(7m away)	56db@rated load/50db@1/4 load	56db@rated load/50db@1/4 load
Dimension	48*31*40cm	48*31*40cm
Weight	15kgs 33lbs	15kgs 33lbs
Fuel Consumption g/kwh	360g/kwh	360g/kwh

SBI 2000ie



FEATURES:

- 4stroke, 50cc, OHV Engine;
- Powerful and Portable;
- Advanced Inverter Technology;
- Pulse Width Modulation provides Super Clean Power;
- Smart Throttle automatically adjusts engine speed to match the load;
- Fuel efficient up to 8+hours on 0.8gal of gasoline;
- AC/DC Output and Cables for 12V marine batteries charging;
- Non-fuse type circuit breaker(NFB)prevents internal circuit ove-load damage.
- Indicator Light for Output Operation.Low Oil Alarm,Over Load Protection;
- 57db at 7m, ultra-quiet performance due to Noise Block body design.

Model	2000ie
Engine	Single-Cylinder,OHV,4-Stroke,Air-Cooled
Displacement	80cc
Ignition system	C.D.I
Starting system	Recoil
Frequency(Hz)	50/60
Voltage(V)	110/120/230/240
D.C. Output	12V 5A
A.C. Output	110/120VRated11.8A 230/240VRated5.6A
Rated Power Output(W)	1800
Max. Power Output(W)	2000
Starting Power(W)	2100
Fuel Tank Capacity	4L 1.05GAL
Continuous Operating Hours	6+hours@rated load/11+hours@1/4 load
Noise(7m away)	58db@rated load/52db@1/4 load
Dimension	54*32*45cm
Weight	20kgs 44lbs
Fuel Consumption g/kwh	360g/kwh

SBI 3000ie



FEATURES:

- 4stroke, 50cc, OHV Engine;
- Powerful and Portable;
- Advanced Inverter Technology;
- Pulse Width Modulation provides Super Clean Power;
- Smart Throttle automatically adjusts engine speed to match the load;
- Fuel efficient up to 8+hours on 0.8gal of gasoline;
- AC/DC Output and Cables for 12V marine batteries charging;
- Non-fuse type circuit breaker(NFB)prevents internal circuit ove-load damage.
- Indicator Light for Output Operation.Low Oil Alarm,Over Load Protection;
- 57db at 7m, ultra-quiet performance due to Noise Block body design.

SBI 3200ie



FEATURES:

- 4stroke, 50cc, OHV Engine;
- Powerful and Portable;
- Advanced Inverter Technology;
- Pulse Width Modulation provides Super Clean Power;
- Smart Throttle automatically adjusts engine speed to match the load;
- Fuel efficient up to 8+hours on 0.8gal of gasoline;
- AC/DC Output and Cables for 12V marine batteries charging;
- Non-fuse type circuit breaker(NFB)prevents internal circuit ove-load damage.
- Indicator Light for Output Operation.Low Oil Alarm,Over Load Protection;
- 57db at 7m, ultra-quiet performance due to Noise Block body design.

Model	3000ie
Engine	Single-Cylinder,OHV,4-Stroke,Air-Cooled
Displacement	150cc
Ignition system	C.D.I
Starting system	Recoil/One Push Start
Frequency(Hz)	50/60
Voltage(V)	110/120/230/240
D.C. Output	12V 8.3A
A.C. Output	110/120VRated24.5A 230/240VRated11.7A
Rated Power Output(W)	2700
Max. Power Output(W)	3000
Starting Power(W)	3000
Fuel Tank Capacity	6L 1.6GAL
Continuous Operating Hours	5+hours@rated load/10+hours@1/4 load
Noise(7m away)	65db@rated load/58db@1/4 load
Dimension	57*35*48cm
Weight	29kgs 64lbs
Fuel Consumption g/kwh	380g/kwh

Model	3200ie
Engine	Single-Cylinder,OHV,4-Stroke,Air-Cooled
Displacement	150cc
Ignition system	C.D.I
Starting system	Recoil/Electric Start/Remote
Frequency(Hz)	50/60
Voltage(V)	110/120/230/240
D.C. Output	12V 8.3A
A.C. Output	110/120VRated27A 230/240VRated13A
Rated Power Output(W)	2900
Max. Power Output(W)	3000
Starting Power(W)	3000
Fuel Tank Capacity	6L 1.6GAL
Continuous Operating Hours	4+hours@rated load/10+hours@1/4 load
Noise(7m away)	65db@rated load/58db@1/4 load
Dimension	58*35*49cm
Weight	32kgs 70.4lbs
Fuel Consumption g/kwh	380g/kwh

LT1900/2000



Model	LT1900	LT2000	
Generator	Rated/Max.A.C.output	0.9kW/1.0kW	1.0W/1.1W
	A.C.Frequency	50Hz	50Hz
	Rated Voltage	220~240V	220~240V
	Engine Model	LT156F/2.9HP	LT156F/2.9HP
Engine	Engine Type	Air cooling; 4-stroke;OHV;single cylinder	
	Ignition System	Transistor magneto	
	Starting System	Recoil	Recoil
	Displacement	93.5cc	93.5cc
	Max. Output	2.1kW	2.1kW
	Fuel Tank Capacity	6L	6L
	Continuous Operating Time	9h	9h
	Min.Fuel Consumption	375g/kW.h	375g/kW.h
	Noise Level	65db	65db
	Lube. Oil Capacity	0.37L	0.37L
Size & Weight	Dimensions(LxWxH)	420*355*355mm	420*355*355mm
	Net Weight	26kg	27kg
	Load Qty. 40'HC/40'GP/20'GP	960/960/430	1246/1770/520

LT6500EB/8000EB/9000EB



Model	LT6500EB	LT8000EB	LT9000EB	
Generator	Rated/Max.A.C.output	5.0kW/5.5kW	6.0kW/6.5kW	7.0kW/7.5kW
	A.C.Frequency	50/60Hz	50/60Hz	50/60Hz
	Rated Voltage	230V/(120/240)V	230V/(120/240)V	230V/(120/240)V
	Engine Model	LT188F/13.0HP	LT190F/15.0HP	LT192FA/16.0HP
Engine	Engine Type	Air cooling ; 4-stroke; OHV; single cylinder		
	Ignition System	Transistor magneto		
	Starting System	Recoil/Electric	Recoil/Electric	Recoil/Electric
	Displacement	389cc	420cc	439cc
	Max. Output	9.6kW	11kW	11.7kW
	Fuel Tank Capacity	25L	25L	25L
	Continuous Operating Time	10h	8h	7h
	Min.Fuel Consumption	313g/kW.h	313g/kW.h	313g/kW.h
	Noise Level	74db	76db	78db
	Lube. Oil Capacity	1.1L	1.1L	1.1L
Size & Weight	Dimensions(LxWxH)	815*525*545mm	815*525*545mm	815*525*545mm
	Net Weight	82kg	85kg	87kg
	Load Qty. 40'HC/40'GP/20'GP	228/228/112	228/228/112	228/228/112

LT1200B



LT2500B/3600B/3900B



Model	LT1200B	LT2500B	LT3600B	LT3900B	
Generator	Rated/Max.A.C.output	0.9kW/1.0kW	2.0kW/2.2kW	2.5kW/2.8kW	
	A.C.Frequency	50/60Hz	50/60Hz	50/60Hz	
Engine	Rated Voltage	230V/120V	230V/120V	230V/120V	
	Engine Model	LT156F/5.5HP	LT168F/6.5HP	LT170F/7.0HP	
	Engine Type	Air cooling ; 4-stroke; OHV; single cylinder			
	Ignition System	Transistor magneto			
	Starting System	Recoil/Electric	Recoil/Electric	Recoil/Electric	Recoil/Electric
	Displacement	93.5cc	163cc	196cc	208cc
	Max. Output	2.1kW	4.1kW	4.8kW	5.1kW
	Fuel Tank Capacity	6L	15L	15L	15L
	Continuous Operating Time	9h	13h	12h	10h
	Min.Fuel Consumption	375g/kW.h	360g/kW.h	360g/kW.h	360g/kW.h
Size & Weight	Noise Level	65db	65db	67db	69db
	Lube. Oil Capacity	0.37L	0.6L	0.6L	0.6L
	Dimensions(LxWxH)	460*370*380mm	605*435*450mm	605*435*450mm	605*435*450mm
	Net Weight	26kg	40kg	43kg	45kg
Load Qty. 40'HC/40'GP/20'GP	960/960/430	550/490/235	550/490/235	550/490/235	

LT6500EN-6/8000EN-6/9000EN-6



Model	LT6500EN-6	LT8000EN-6	LT9000EN-6	
Generator	Rated/Max.A.C.output	5.0kW/5.5kW	6.0kW/6.5kW	7.0kW/7.5kW
	A.C.Frequency	50/60Hz	50/60Hz	50/60Hz
Engine	Rated Voltage	230V/(120/240)V	230V/(120/240)V	230V/(120/240)V
	Engine Model	LT188F/13.0HP	LT190F/15.0HP	LT192FA/16.0HP
	Engine Type	Air cooling ; 4-stroke; OHV; single cylinder		
	Ignition System	Transistor magneto		
	Starting System	Recoil/Electric	Recoil/Electric	Recoil/Electric
	Displacement	389cc	420cc	439cc
	Max. Output	9.6kW	11kW	11.7kW
	Fuel Tank Capacity	25L	25L	25L
	Continuous Operating Time	10h	8h	7h
	Min.Fuel Consumption	313g/kW.h	313g/kW.h	313g/kW.h
Size & Weight	Noise Level	74db	76db	78db
	Lube. Oil Capacity	1.1L	1.1L	1.1L
	Dimensions(LxWxH)	815*530*560mm	815*530*560mm	815*530*560mm
	Net Weight	82kg	85kg	87kg
Loading 40'HC/40'GP/20'GP	228/228/112	228/228/112	228/228/112	

3GF-M/ME/M3/ME3



5GF-ME/6GF-ME/7GF-ME
5GF-ME3/6GF-ME3/7GF-ME3



Model	3GF-M	3GF-M3	3GF-ME	3GF-ME3
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Max. Ac Output	3.3/3.6kW	3.3/3.6kW	3.3/3.6kW	3.3/3.6kW
Rated Ac Output	3.0/3.2kW	3.0/3.2kW	3.0/3.2kW	3.0/3.2kW
DC Output	12V/8.3A	12V/8.3A	12V/8.3A	12V/8.3A
Rated Voltage	220V	220/380V	220V	220/380V
Power Factor (φ)	1.0	0.8	1.0	0.8
Phase	Single-phase	Three-phase	Single-phase	Three-phase
Excitation System	Self-excitation	Self-excitation	Self-excitation	Self-excitation
Dimension (LxWxH)	690*470*570mm	690*470*570mm	690*470*570mm	690*470*570mm
Net Weight	69kg	69kg	69kg	69kg
Engine Model	LT178F	LT178F	LT178F	LT178F
Type	Single-cylinder, vertical; 4-stroke; air-cooled; direct-injection			
Displacement	296cc	296cc	296cc	296cc
Fuel Tank Capacity	15L	15L	15L	15L
Lube. Oil Capacity	1.1L	1.1L	1.1L	1.1L
Starting System	Manual/Electric Optional	Manual/Electric Optional	Manual/Electric Optional	Manual/Electric Optional
Low Oil Alarm System	With	With	With	With
Load Qty. 40'HC/40'GP/20'GP	304/304/144	304/304/144	304/304/144	304/304/144

Model	5GF-ME/5GF-ME-F3	6GF-ME/6GF-ME-F3	7GF-ME/7GF-ME-F3
Frequency	50/60Hz	50/60Hz	50/60Hz
Max. Ac Output	4.8/5.5kW	6.0/6.5kW	6.8/7.0kW
Rated Ac Output	4.4/5.0kW	5.5/6.0kW	6.3/6.5kW
DC Output	12V/8.3A	12V/8.3A	12V/8.3A
Rated Voltage	220V	220V	220V
Power Factor (φ)	1.0	1.0	1.0
Phase	Single-phase	Single-phase	Single-phase
Excitation System	Self-excitation	Self-excitation	Self-excitation
Dimension (LxWxH)	730*470*700mm/770*535*660mm	760*500*650mm	760*500*650mm
Net Weight	120kg	160kg	163kg
Engine Model	LT186F	LT188FD	LT192FD
Type	Single-cylinder, vertical; 4-stroke; air-cooled; direct-injection		
Displacement	406cc	455cc	498cc
Fuel Tank Capacity	15L	15L	15L
Lube. Oil Capacity	1.65L	1.65L	1.65L
Starting System	Manual/Electric Optional	Manual/Electric Optional	Manual/Electric Optional
Low Oil Alarm System	With	With	With
Load Qty. 40'HC/40'GP/20'GP	210/210/102	210/210/102	210/210/102

5GF-LDEF/LDEF3



Model	5GF-LDEF	5GF-LDEF3
Frequency	50/60Hz	50/60Hz
Max. Ac Output	4.8/5.5kW	5.3/5.5kW
Rated Ac Output	4.4/5.0kW	4.8/5.0kW
DC Output (V-A)	12V/8.3A	12V/8.3A
Rated Voltage	220V	220/380V
Power Factor (φ)	1.0	0.8
Phase	Single-phase	Three-phase
Excitation System	Self-excitation	Self-excitation
Dimension (LxWxH)	990*580*770mm	990*580*770mm
Net Weight	165kg	167kg
Engine Model	186F	186F
Noise Level	70db	70db
Type	Single-cylinder, vertical; 4-stroke; air-cooled; direct-injection	
Displacement	406cc	406cc
Fuel Tank Capacity	16L	16L
Lube. Oil Capacity	1.65L	1.65L
Starting System	Electric start	Electric start
Low Oil Alarm System	With	With
Load Qty. 40'HC/40'GP/20'GP	126/126/60	126/126/60

